

**NEW ADDITIONS**



# 4 LEG DOME with HOLE

**Stable Forces per Batch Number**

**Excellent Tactile Effect**

**100% Traceability per Batch Number**

**Competitive Pricing**

**Superior Quality**

**Used in a multitude of Industries, such as:  
Membrane Switch, Automotive, Consumer  
Electronics, Medical, Appliance, etc**

**Suitable for LED Lighting**

**RoHS Compliant**

<b>Contact Configuration</b>	SPST, Normally Open	<b>Contact Resistance with Gold or Silver Plating</b>	<100 ohms
<b>Contact Bounce (on)</b>	<0.3ms	<b>Voltage/Current Maximum</b>	<1 ohm
<b>Contact Bounce (off)</b>	<6ms	<b>Breakdown Voltage</b>	12mA @ 24 Volts DC, RL
<b>Operating Temperature</b>	-55°C to 125°C	<b>Material</b>	Over 200 Volts
<b>Storage Temperature</b>	-55°C to 125°C	<b>Life Expectancy</b>	Stainless Steel Type 304
<b>Humidity</b>	0-97% (no condensation)		Up to 1 Million

	Part No	Force	Size	Dimensions (mm)				
				Thickness	A	B	C	D Hole Ø
	MD 8.4 4 LLL-H-280N	280g	8.4mm	0.08	8.4	1.79	0.45	1.8
	MD 8.4 4 LLL-H-400G	400g	8.4mm	0.10	8.4	1.79	0.48	1.8
	MD 10 4 LEG-H-280N	280g	10.0mm	0.10	10.0	2.28	0.45	2.5
	MD 10 4 LEG-H-280G	280g	10.0mm	0.10	10.0	2.28	0.52	2.5
	MD 10 4 LEG-H-400N	400g	10.0mm	0.10	10.0	2.28	0.52	2.5
	MD 12 4 LEG-H-350N	350g	12.0mm	0.10	12.0	2.12	0.63	3.0
	MD 12 4 LEG-H-350G	350g	12.0mm	0.10	12.0	2.12	0.63	3.0
	MD 14 4 LEG-H-400N	400g	14.0mm	0.12	14.0	2.79	0.72	3.5

Plating Suffix at end of Part Number: N = Nickel, G = Gold

**MEMCON (Asia) Limited**  
Units 5/6 6/F Westley Square  
48 Hoi Yuen Rd Kwun Tong Hong Kong  
T +852 3741 1411 F +852 3747 8980  
www.memcon.asia sales@memcon.asia

**MEMCON Limited**  
Unit 8 Campus Five Third Avenue Letchworth  
Hertfordshire SG6 2JF United Kingdom  
T +44 (0) 1462 371477 F +44 (0) 1462 677499  
www.memcon.eu sales@memcon.eu

**MEMCON North America**  
6000 Red Arrow Hwy Unit I  
Stevensville Michigan 49127 USA  
T +1 269 281 0478 F +1 269 593 5952  
www.memcon.net sales@memcon.net