



BLACK & WHITE DOUBLE SIDED SPACER TAPE


Our range of high performance spacer tapes have been specifically developed for use in membrane switch applications and associated products. The spacer tapes which utilise high performance adhesive, provide a good level of initial tack and a high level of adhesive strength.

Developed for use in the harshest of conditions, our spacer tapes demonstrate outstanding resistance to hostile environments. They are ideally suited for die-cutting.

Our spacers are available in both double sided and single sided construction, in a wide variety of polyester carrier and adhesive thicknesses.


The MS series spacer tapes provide a high quality product at a price positioned to help our customers compete in this competitive market.

Sheet sizes of 915 x 610mm (S1) & 1000 x 700mm (S2) are available. Standard roll size 100M x 960mm



White Printed Release Paper
Black Acrylic Adhesive
Solid Black Polyester Film
Black Acrylic Adhesive
White Release Paper

Black	Total Thickness mm	Carrier Thickness mm	Adhesive Thickness	Carrier Material/ Colour	Adhesion to Steel N/25mm	Adhesion to PET	Holding Power, 25mm 1kg 25°C	Working Temp	Short Temp
MSD125-50A50BB	0.125	0.025	0.050/0.050	PET Black	≥18	≥16	≥4.5	-30~120°C	200°C
MSD225-50A50BB	0.225	0.125	0.050/0.050	PET Black	≥18	≥16	≥4.5	-30~120°C	200°C



White Printed Release Paper
Acrylic Adhesive
White Polyester Film
Acrylic Adhesive
White Release Paper

White	Total Thickness mm	Carrier Thickness mm	Adhesive Thickness	Carrier Material/ Colour	Adhesion to Steel N/25mm	Adhesion to PET	Holding Power, 25mm 1kg 25°C	Working Temp	Short Temp
MSD150-50A50W	0.150	0.050	0.050/0.050	PET White	≥18	≥16	≥4.5	-30~120°C	200°C

The performance characteristics are those results obtained in our laboratory.

Memcon makes no warranties and assumes no liability in connection with any use of this information.

Before adopting our products for commercial use, the user assumes responsibility for determining fitness of use in their particular application and process.

MEMCON (Asia) Limited
Units 5/6 6/F Westley Square
48 Hoi Yuen Rd Kwun Tong Hong Kong
T +852 3741 1411 F +852 3747 8980
www.memcon.asia sales@memcon.asia

MEMCON Limited
Unit 8 Campus Five Third Avenue Letchworth
Hertfordshire SG6 2JF United Kingdom
T +44 1462 371477 F +44 1462 677499
www.memcon.eu sales@memcon.eu

MEMCON North America
6000 Red Arrow Hwy Unit I
Stevensville Michigan 49127 USA
T +1 269 281 0478 F +1 269 593 5952
www.memcon.net sales@memcon.net